

CARE AND MAINTENANCE GUIDE

DURATIQUE™ STAINLESS STEEL ANTIQUE HARDWARE

LIT-CMG-DURATIQUE

To help you care for the DURATIQUE™ hardware range please follow the guidelines below.

During installation and whilst building work is being carried out the hardware should be covered to protect it from dust, dirt and scratching.

Immediately after fitting and installation

- Product should be cleaned using a soft cloth and mild soapy water then dried immediately with a clean, soft cloth.

Monthly Care and Maintenance

- Clean regularly with a soft, dry cloth or duster.
- Product should be washed monthly using a soft cloth and mild soapy water then dried immediately with a clean, soft cloth - especially if fitted on or near the coast.
- Fingerprints can be removed by washing product as above.
- The above procedure should be followed with an application of good quality, non-abrasive car wax polish, gently applied, to protect the finish.

Six Monthly Care and Maintenance

- Lubricate any moving parts with a suitable PTFE Grease such as GLS200 available from www.coastal-group.com.

Please Note

- DO NOT use oily rags or greasy cloths when wiping the product surface.
- DO NOT use bleach, abrasive cleaners, caustic or acid based cleaning materials, or detergents containing chloride, or any other strong household cleaning products.
- DO NOT use abrasive materials, files or other hard objects against the product surface.
- This product should be protected from dust and dirt during any construction work.



COASTAL

Shaping the future.