
### CASEMENT WINDOW HARDWARE

## TRITUS HINGE QUANTITY CHART & HANDING INFORMATION

# FH70 and FH80

Height (mm)	Width (mm)			
	< 500	501-600	601-700	701-800
1401 - 1500		3(3)	3(3)	3(4)
1301 - 1400	2(3)	3(3)	3(3)	3(4)
1201 - 1300	2(3)	3(3)	3(3)	3(4)
1101 - 1200	2(3)	3(3)	3(3)	3(4)
1001 - 1100	2(3)	3(3)	3(3)	3(3)
901 - 1000	2(2)	2(2)	2(2)	3(3)
801 - 900	2(2)	2(2)	2(2)	3(3)
701 - 800	2(2)	2(2)	2(2)	3(3)
601 - 700	2(2)	2(2)	2(2)	
501 - 600	2(2)	2(2)	2(2)	
< 500	2(2)			



### **Hinge Quantity Chart**

The chart above helps you select how many hinges you require based on your sash height & width. The numbers in brackets are the number of hinges required per sash when using triple glazing.

### **Hinge Handing Information**

The hinges for this system are handed from the outside. They are cranked and designed to fit the Tritus groove detail, making them a handed product.

The bottom part of the hinge with the pin fits into the 12mm groove in frame, with the pin uppermost, the other half of hinge fits into the 17mm groove in the sash with the hole facing downwards.

