

COFIRM DOUBLE SIDED GLAZING TAPE

Product Code: CF16

LIT-DC-CF16



- CoFirm is a high performance double sided glazing tape
- Made from closed cell PE foam tape which is ideal for bonding difficult or dissimilar surfaces such as Durodeen beads, Georgian bars, Astragal bars, fixing beads and for fixing glass against the rebate
- Easy to apply
- High initial tack and greater long-term bond than many other glazing tapes on the market
- Resistant to UV exposure and temperature variations
- Resistant to stress and vibration
- Provides an excellent seal
- Successfully used in our Part Q Tests



COASTAL

Shaping the future.

FINISHES:



BK
Black



WH
White

PART NUMBER	PRODUCT DESCRIPTION	FINISH	UNITS
CF1610-BK	1.6 x 10mm CoFirm tape	BK	46m Coil
CF1610-WH	1.6 x 10mm CoFirm tape	WH	46m Coil
CF1612-BK	1.6 x 12mm CoFirm tape	BK	46m Coil
CF1612-WH	1.6 x 12mm CoFirm tape	WH	46m Coil
CF1615-BK	1.6 x 15mm CoFirm tape	BK	46m Coil
CF1615-WH	1.6 x 15mm CoFirm tape	WH	46m Coil
CF1618-BK	1.6 x 18mm CoFirm tape	BK	46m Coil
CF1618-WH	1.6 x 18mm CoFirm tape	WH	46m Coil
CF1620-BK	1.6 x 20mm CoFirm tape	BK	46m Coil
CF1620-WH	1.6 x 20mm CoFirm tape	WH	46m Coil
CF1622-BK	1.6 x 22mm CoFirm tape	BK	46m Coil
CF1622-WH	1.6 x 22mm CoFirm tape	WH	46m Coil
CF1624-BK	1.6 x 24mm CoFirm tape	BK	46m Coil
CF1624-WH	1.6 x 24mm CoFirm tape	WH	46m Coil

SPECIFICATION:

- Liner:** Standard - yellow, Kraft, 90gsm, d/s silicon coated, option - HDPE film, 140gsm, blue
- Carrier:** Medium density (67kg) polyolefin foam 1.5mm thick
- Adhesive:** Specially modified polyacrylat - H+ class, Deposition- 65gsm, cross linked,

PRODUCT DATA:

- Ahesion:** According to AFERA 4001 (10min dwell@RT)

Glass	19N/25mm
Steel	18N/25mm
PVC	16N/25mm
PP	15N/25mm
- Temperature Resistance:**

From -40°C to +70°C (long term) +90°C (short term)
According to ISTM D3654
Method: area of 6.25cm² with 0.5kg load @700C for 10,000 minutes
Result: No change



COASTAL
Shaping the future.