



## RS10 Safety Catch Restrictor

Restrictors for PVCu and Timber Windows



# RS10 Safety Catch Restrictor

Restrictors for PVCu and Timber Windows



## RS10 Safety Catch Features:

- 5 screws- 3 easy steps
- Restricts opening to 50mm - 100mm
- Push button release
- Non-locking and Grub screw locking options available
- Automatically restricts window opening
- Perfect for retrofitting to existing windows
- Available in White or brown

**Key features:**

The robust design incorporates the following features:

- Conforms to BS6375 Part 2. Load bearing capability of Safety Devices.
- The RS10 automatically prevents the opening of a window greater than 50mm - 100mm (depending on the positioning on the window).
- The RS10 locking bar can be released for full opening of the sash by keeping the push button depressed.
- The RS10 will automatically re-engage when the window is closed.
- Surface mounted vertically or horizontally on both outward opening and inward opening windows, it can be retrofitted to existing windows as an additional security and safety device.
- 3mm adjustment of steel hook possible for correct operation.
- Easily fitted using 5 screws. The steel hook is fixed with three screws (for PVCu windows fixing into reinforcement is recommended). Drill jigs available for both site fixing or factory fixing.
- An extensive range of packers and mounting blocks available.
- 1mm shims available for optimum positioning of steel hook.
- Purpose designed to provide high levels of child safety and increased security for both new and existing windows, together with a lockable 50mm vent position.
- Can be fitted by eye utilising aligning mark on body of Safety Catch. The line can be transferred using a pencil to indicate the position for the hook base plate.
- The RS10 is available in white and brown as standard.

