

MAKING HARD WORK EASIER

SLP20XP-GLN



Applications

Glass retaining strips


Features & Benefits

- Easy side loading that allows you to change brad length without adjusting tool, plus E-Z Clear jam clearance
- Reduces fatigue throughout comfort-grip handle and the best balance and lowest recoil in the industry
- Superior power (40% more than comparable tools) makes it suitable for use on hardwood, plastics, and particleboard
- Oil-free design means easier maintenance and no lubrication to stain fine woods
- Precision-firing keeps work surface free of damage
- Rugged composition enables magazine to withstand onthe-job stress
- Requires minimum maintenance, with only two movable O-rings for virtually trouble-free upkeep
- Repair is easy, using only two Allen wrenches and the doityourself SENCO Parts Kit
- Comes complete in its own heavy-duty plastic case
- Muffler ensures quieter operation

Glazing brad nailer

Technical specificatio	ns	
Dimension (LxWxH)	275x50x225 mm	
Net weight	1,17 kg	
Firing mode	Restrictive	
Air inlet	1/4" female NPT	
Operating pressure	4,8 - 8,3 bar	
Air consumption (at 60 shots per minute)	54 l/m	
Operating temperature range	-18 - 49 ºC	
Sound pressure level (Lpa)	79 dB	
Sound power level (Lwa)	88 dB	
Vibration level	under declaraton limit m/ s ²	
Magazine capacity	110 pieces	
Gauge	18 ga.	
Collation type 1	Glue collated	
Collation type 2	Glue collated	
Collation angle	0 o	

Fastener specification



Description	Art. Nr.	EAN code
SLP20XP GLN, glazing brad nailer 1,2mm (AX)	WCE0485	8715274044927

www.senco.eu